



Color: Black with green stripe

Temperature range: -40°C +125°C

Features: Flexible duct made in thermoplastic rubber with a steel spiral reinforcement embedded between the two layers. Light and flexible is extremely resistant to high temperatures, chemicals and abrasion.

APPLICATIONS: suction of hot air and fumes in chemical plants and shipyards.

TECHNICAL DATA:

Part Number	Inside Ø	Min. Wall Thickness	Max. Wall Thickness	Vacuum	Bending radius	Roll Length	Volume
	mm	mm	g/m	m H2O	mm	m	m3
TPR1.5-VULCANO	38	0,4	190	2,0	30	20	0,074
TPR2-VULCANO	51	0,4	250	2,0	40	20	0,108
TPR2.5-VULCANO	63	0,4	310	1,7	55	20	0,150
TPR3-VULCANO	76	0,5	470	1,7	65	20	0,232
TPR3.5-VULCANO	90	0,5	580	1,6	75	20	0,294
TPR4-VULCANO	102	0,6	620	1,3	85	15	0,286
TPR4.5-VULCANO	110	0,6	660	1,2	90	15	0,318
TPR5-VULCANO	127	0,65	840	1,0	105	15	0,405
TPR6-VULCANO	152	0,65	1030	0,8	125	15	0,544
TPR8-VULCANO	203	0,65	1500	0,4	165	15	1,157
TPR10-VULCANO	254	0,65	1950	0,4	210	10	1,197
TPR12-VULCANO	305	0,65	2400	0,3	250	10	1,633

