

ANTI-STATIC SAND BLAST HOSE

175 PSI / 12 BAR

MADE IN ITALY

TECHNOFLEX - ITALY ANTI-STATIC SAND BLAST HOSE W. P. 175 PSI/12 BAR

TechnoFlex Sand Blast Hose - 175 PSI / 12 BAR

Engineered with a specially formulated extra-thick tube compound to significantly extend service life in demanding sandblasting applications. Designed for enhanced flexibility and kink resistance, reducing operator fatigue and improving handling efficiency. The rugged outer cover provides outstanding resistance to abrasion, harsh weather conditions, and prolonged exposure to tough working environments, ensuring reliable and long-lasting performance.

- **Temperature Range:**
 - -30°C to +80°C
- **Reinforcement:**
 - Multiple textile plies.
- **Tube:**
 - Black Natural rubber blend.
- **Cover:**
 - Black Natural rubber blend.
- **Standard Length:**
 - 20m / 60m
- **Safety Factor:**
 - 4:1

HOSE I.D.		Tube. Thickness		HOSE O.D.		WORKING PRESSURE		BURST PRESSUER		WEIGHT
inch	mm	inch	mm	inch	mm	bar	psi	bar	psi	Kg/m
½	12.7	¼	6.4	1.209	30.7	175	12	700	48	0.90
¾	19.1	¼	6.4	1.459	37.1	175	12	700	48	1.11
1	25.4	¼	6.4	1.709	43.4	175	12	700	48	1.31
1 ¼	31.8	¼	6.4	1.959	49.8	175	12	700	48	1.52
1 ½	38.1	¼	6.4	2.209	56.1	175	12	700	48	1.72
1 ¾	44.5	¼	6.4	2.459	62.5	175	12	700	48	1.93
2	50.8	¼	6.4	2.709	68.8	175	12	700	48	2.13
2 ½	63.5	¼	6.4	3.256	82.7	175	12	700	48	2.73
3	76.2	¼	6.4	3.756	95.4	175	12	700	48	3.17

Authorized Distributor:
MOHAMMED AHMED AL-AWANI TRADING COMPANY

Dewatering Pump Sales | Dewatering Accessories | Hoses & Fittings | Pump Parts | Pump Rental | Pump Service

